



# P2 Cupped Disposable Respiratory Face Masks

## Respiratory Protection | P2 Cupped

### CLASS P2

For mechanically & thermally generated particles. These filters have a higher efficiency to deal effectively with smaller, thermally generated particles such as welding fumes, they are also recommended for infection control applications. eg. TB, Flu or other infectious disease environments.



20027163



20027164  
With Valve

### Order Code(s):

- 20027163 (P2 Cupped)
- 20027164 (P2 Cupped with Valve)

### Retail Box/Carton Dimensions & Qty:

- 20027163 (P2 Cupped)  
Retail: 135mm(W) x 160mm(H) x 120mm(D) - 20 Masks per Box  
Carton: 620mm(W) x 340mm(H) x 290mm(D) - 400 Masks per Carton
- 20027164 (P2 Cupped with Valve)  
Retail: 135mm(W) x 160mm(H) x 120mm(D) - 10 Masks per Box  
Carton: 620mm(W) x 340mm(H) x 290mm(D) - 200 Masks per Carton

### Compliance/Standard:



### Features & Benefits:

- Nose clip adjusts to fit most face shapes & sizes.
- Light weight & easy to use.
- Unrestricted field of vision.
- Low profile allows for wearing with glasses or safety goggles.
- Exhalation valve (20027164) for added wearer comfort expels hot air from the respirator faster, keeping the wearer cooler.
- Welded elastic head straps.

### Applications/Industry:

- Infectious disease environments
- Dusty work shops
- Sanding & grinding
- Cutting & sawing & crushing
- Welding
- Smoke environments
- Farming & Agriculture